



PRODUCT INFORMATION

Chakrol CF4 15W-40

Description

Chakrol CF4 15W-40 is a premium quality High Performance Diesel Engine Oil. Chakrol CF4 15W-40 engine oils are designed with high detergent additive system. These oils have excellent Total Base Number (TBN) retention to ensure protection throughout the oil drain period. It has enhanced protection against corrosion and wear.

Chakrol CF4 15W-40 provides reliable all-year round performance in the application for which they are intended.

Applications

Chakrol CF415W-40 oils are designed for use in all new generation diesel engines.

Supply Options

Despatched and delivered typically in 210 Ltr HDPE Barrels, 50 Ltr, 20 Ltr & 7.5 Ltr packs. Customer specific packs sizes are available on request to suit specific requirements.

Specifications: Meets API CF4, ACEA E2, MB228.1 & E-DL4 of IS: 13656-93.

Property	SAE VISCOSITY GRADE	Test Method
	15W40	
Density, Kg/L 15.5 C	0.870	ASTM D 1298
Kin. Visc@ 100°C, cSt	14.0 -16.0	ASTM D 445
Viscosity Index	130 min	ASTM D 2270
Flash Point, COC	220 °C min	ASTM D 92
Pour Point °C,	-27 °C max	ASTM D 97
TBN, mgKOH/gm	10.0 min.	ASTM D2896

- *The above data is indicative of recent averages values only. Minor variations that do not affect product performance or quality may be expected in manufacture.*
- **Specific requirements can be custom made on request.**
- *The above information is supplied to the best of our knowledge and belief, on the basis of the current state-of-art and our own development work. Subject to amendment.*

For further details please contact:

M/s Sri Rama Lubricants.,

153/5/2, Manapet, Kanniakoil, Pondicherry 607402, INDIA .Tel: (+91)413 2611518.

Web site : www.chakrol.com, e-mail id:sales@chakrol.com